


| | | 228 | | | |
|---------------|---------------------|-----------------|--------|-----|--|
| | | WPV-MFD | | | |
| | DN | 50 | 80 | 100 | |
| DIN ISO 4064 | Q _n 3/ | 15 | 40 | 60 | |
| | Q _{max} 3/ | 35 | 120 | 230 | |
| () | Q _{max} 3/ | 90 | 200 | 300 | |
| | Q _n 3/ | 2,5 | | | |
| | Q 3/ | 0,0375 | | | |
| | Q _{min} 3/ | 0,020 | | | |
| | 3/ | 2,2 | 2,3 | | |
| | 3/ | 1,0 | 1,5 | | |
| DIN 19625 | L | 270 | 300 | 360 | |
| DIN ISO 4064 | L | 300 | | 350 | |
| | H | 130 | 140 | | |
| | h | 75 | 93 | 105 | |
| | H1 | 136 | 146 | | |
| | A | 245 | 280 | | |
| | B | 160 | 180 | | |
| | | 165 | 200 | 220 | |
| | | 125 | 160 | 180 | |
| | | 18 | | | |
| | | 4 | *(4) 8 | 8 | |
| | 3 | 10 ⁶ | | | |
| | 3 | 10 ⁵ | | | |
| | | 17,4 | 25,5 | 29 | |
| | | 6,3 | 9,3 | 9,3 | |
| (Reed) BR 570 | / | 100/1.000 | | | |
| BR 573 | / | 1,0 | | | |
| , NZ () | / | 100 oder 1.000 | | | |
| (Reed) | / | 1,0 | | | |
| BONYTO- - - + | / | 1,0 | | | |

*)

| | | | | |
|-----|-----|----------------------|--------------------|------------|
| 228 | 50 | WPV-MFD/TYRBOT-COMBY | . B | 228 000 01 |
| 228 | 80 | WPV-MFD/TYRBOT-COMBY | 8- ./DIN 2501, . B | 228 000 03 |
| 228 | 80 | WPV-MFD/TYRBOT-COMBY | 4- ./DIN 2533, . B | 228 000 02 |
| 228 | 100 | WPV-MFD/TYRBOT-COMBY | 360 , . B | 228 000 04 |

(626)



| | | | | | | |
|-----|--------|-----|---|-----|----|------------|
| 50 | 327±20 | 165 | 4 | 125 | 19 | 626 000 10 |
| 80 | 397±40 | 200 | 8 | 160 | 19 | 626 000 12 |
| 80 | 397±40 | 200 | 4 | 160 | 19 | 626 000 11 |
| 100 | 442±25 | 220 | 8 | 180 | 19 | 626 000 13 |